



IMPACT CONVEYOR BED SKID BAR

AEG Impact Conveyor Bed Skid bars are dual hardness polyurethane, 60 Shore A base for Impact Absorption and 60 Shore D top for Sliding Co- Efficiency. The polyurethane layers are chemically bonded to each other and also chemically and mechanically bonded to an extruded Aluminium profile for quick, safe and secure installation.

Specifically designed to absorb the impact force of falling aggregate onto conveyor belts and prevent damage in load zone conveyor impact cradles and belt support systems.

Due to both layers being polyurethane, the AEG Impact Conveyor Bed Skids have increased abrasion resistance and life span over conventional Rubber and UHMW combination products.

Dimensions:

- 80mm HT x 100mm WD x 1000mm LNG;
- 80mm HT x 100mm WD x 1250mm LNG;
- 80mm HT x 100mm WD x 1500mm LNG;

Fixing method:

- Integrated Aluminium rail,
- Sliding T-bolt with washer

Materials:

- Polyurethane 60 Shore A
- Polyurethane top layer 60 Shore D
- Extruded Aluminium (high alloy) profile



Christchurch

P 0800 880 233

F 0800 880 234

sales@advanced-eng.co.nz

Brisbane

P 61 7 3713 7744

F 61 7 3713 7788

sales@advanced-eng.com.au

Melbourne

P 61 3 9363 1577

F 61 3 9363 6099

sales@advanced-eng.com.au

For more information on our products and services visit our website at www.advanced-engineering-group.com