



RUBBER CONVEYOR SKIRTING

Black Natural Skirting Rubber (65 shore 'A' & Tensile Strength: 3 MPA), the traditional product of choice and is still widely used today in the quarry, mining and materials handling industries. AEG keep a wide range in stock for your immediate access. Sold in 30m rolls.



Product Code Description

RUB10-100	10mm x 100mm x 30m
RUB10-150	10mm x 150mm x 30m
RUB10-200	10mm x 200mm x 30m
RUB10-250	10mm x 250mm x 30m
RUB10-300	10mm x 300mm x 30m
Other specifications also available: 6mm, 16mm & 19mm Thick	

Product Code Description

RUB12-100	12mm x 100mm x 30m
RUB12-150	12mm x 150mm x 30m
RUB12-200	12mm x 200mm x 30m
RUB12-250	12mm x 250mm x 30m
RUB12-300	12mm x 300mm x 30m
Other specifications also available: 6mm, 16mm & 19mm Thick	



Orange Skirting Rubber (40 shore 'A' & Tensile Strength: 16 MPA) has better abrasion resistant properties with up to 3-5 times the wear life of black natural skirting rubber. Sold in 15m rolls

Product Code Description

RUB10-100-OR	10mm x 100mm x 15m
RUB10-150-OR	10mm x 150mm x 15m
RUB10-200-OR	10mm x 200mm x 15m
Other specifications also available: 6mm, 16mm & 19mm Thick	

Product Code Description

RUB12-100-OR	12mm x 100mm x 15m
RUB12-150-OR	12mm x 150mm x 15m
RUB12-200-OR	12mm x 200mm x 15m
Other specifications also available: 6mm, 16mm & 19mm Thick	

*Other specifications available on request.

www.advanced-engineering-group.com

Christchurch

P 0800 880 233

F 0800 880 234

sales@advanced.eng.co.nz

Brisbane

P 61 7 3713 7744

F 61 7 3713 7788

sales@advanced-eng.com.au

Melbourne

P 61 3 9363 1577

F 61 3 9363 6099

sales@advanced-eng.com.au