



Woven Wire Screencloth Specifications Square Apertures - High Tensile Wire

Aperture (mm)	Wire (mm)	Open Area %	AU	NZ
150.0	12.50	85	✓	✓
125.0	12.50	83	✓	✓
100.0	12.50	79	✓	
100.0	11.20	81	✓	✓
90.0	11.20	79	✓	
85.0	11.20	79	✓	✓
80.0	10.00	79	✓	
75.0	11.20	76	✓	✓
70.0	10.00	77	✓	✓
70.0	8.0	81	✓	
65.0	12.50	70	✓	
65.0	10.00	74	✓	
65.0	8.00	79	✓	✓
63.0	10.00	74	✓	✓
60.0	11.20	71	✓	
57.0	10.00	72	✓	✓
55.0	11.20	69	✓	
55.0	8.00	76	✓	✓
50.0	10.00	70	✓	✓
50.0	8.00	74	✓	✓
45.0	10.00	67	✓	
45.0	8.00	72	✓	✓
42.0	8.00	61	✓	
42.0	7.10	73	✓	✓
40.0	10.00	64	✓	✓
40.0	8.00	69	✓	✓
38.0	8.00	68	✓	
38.0	7.10	71	✓	✓
35.5	10.00	61	✓	
35.0	8.00	66	✓	✓
32.0	7.10	67	✓	✓
31.5	10.00	58	✓	✓
31.5	8.00	64	✓	✓

Aperture (mm)	Wire (mm)	Open Area %	AU	NZ
30.0	8.00	62	✓	
30.0	7.10	65	✓	✓
28.0	8.00	60	✓	✓
26.2	6.30	65	✓	
25.3	7.10	61	✓	✓
25.0	8.00	57	✓	
25.0	6.30	64	✓	✓
24.0	8.00	56	✓	✓
22.7	6.3	61		✓
22.4	8.0	54	✓	
22.4	6.30	61	✓	
22.1	7.10	57	✓	✓
21.7	6.30	60	✓	✓
21.0	7.10	56	✓	✓
20.2	6.3	58		✓
20.0	8.00	51	✓	✓
20.0	6.30	58	✓	
20.0	5.00	64	✓	
19.2	6.3	57		✓
19.0	6.30	57	✓	
19.0	5.00	63	✓	✓
18.4	5.60	59	✓	✓
18.0	6.30	55	✓	
18.0	5.00	61	✓	
18.0	4.00	67	✓	
17.5	6.3	60		✓
17.3	5.0	60		✓
16.0	6.30	52	✓	✓
16.0	5.60	55		✓
16.0	5.00	58	✓	✓
16.0	4.00	64	✓	
15.3	5.00	56		✓
15.0	5.00	56	✓	
15.0	4.00	62	✓	
14.0	5.00	54	✓	✓
14.0	4.00	60	✓	
13.4	5.00	53	✓	✓
13.0	4.00	58	✓	✓
12.5	5.00	51	✓	✓
12.5	4.00	58	✓	

Aperture (mm)	Wire (mm)	Open Area %	AU	NZ
12.4	3.15	63		✓
12.0	5.00	50	✓	
12.0	3.15	63	✓	
11.8	4.00	56		✓
11.5	5.00	49		✓
11.2	4.00	54	✓	✓
11.2	3.15	61	✓	✓
10.2	4.00	52	✓	✓
10.0	5.00	44	✓	
10.0	3.15	58	✓	
9.0	4.00	48	✓	
9.0	3.15	55	✓	✓
8.4	4.00	46	✓	✓
8.0	4.00	44	✓	
8.0	3.15	51	✓	✓
7.4	3.15	48		✓
7.2	4.00	41	✓	✓
7.1	3.15	48	✓	
7.1	2.80	51	✓	✓
6.8	3.15	47		✓
6.3	3.15	44	✓	
6.2	3.15	44		✓
5.8	3.15	42	✓	✓
5.7	2.80	45	✓	✓
5.3	3.15	38		✓
5.0	3.15	38	✓	
5.0	2.50	44	✓	
5.0	2.00	50	✓	✓
4.8	1.60	56		✓
4.5	2.50	41	✓	✓
4.0	2.50	38	✓	✓
4.0	1.60	51	✓	
3.8	2.5	36		✓
3.8	2.00	43	✓	✓
3.8	1.60	50		✓
3.4	2.0	40		✓
3.2	2.00	38	✓	✓
3.15	2.00	36	✓	
3.0	2.00	36		✓
3.0	1.50	43	✓	✓
2.5	1.50	39	✓	✓
2.0	1.00	44	✓	✓

Varying apertures, wire diameters and crimp types are available upon request, ask one of our expert sales representatives for further information.

Note:
Specs held in each country
AU = Australia
NZ = New Zealand

www.advanced-engineering-group.com

Christchurch
P 0800 880 233
F 0800 880 234
sales@advanced.eng.co.nz

Brisbane
P 61 7 3713 7744
F 61 7 3713 7788
sales@advanced-eng.com.au

Melbourne
P 61 3 9363 1577
F 61 3 9363 6099
sales@advanced-eng.com.au