

RUBBER CONVEYOR SKIRTING

Black Natural Skirting Rubber

(65 shore 'A' & Tensile Strength: 3 MPA), the traditional product of choice and isstill widely used today in the quarry, mining and materialshandling industries. AEG keep a wide range in stock for your immediate access.



Product Code & Description	AU	NZ	Product Code & Description	AU	NZ
10-100 10mm x 100mm x 30m	✓		12-100 12mm x 100mm x 30m	✓	
10-150 10mm x 150mm x 30m	√		12-150 12mm x 150mm x 30m	√	
10-150 10mm x 150mm x 15m		✓	12-200 12mm x 200mm x 30m	√	
10-200 10mm x 200mm x 30m	✓		12-200 12mm x 200mm x 15m		✓
10-250 10mm x 250mm x 30m	√		12-250 12mm x 250mm x 30m	√	
10-300 10mm x 300mm x 30m	✓		12-300 12mm x 300mm x 30m	✓	

^{*}Other specifications also available



Orange Skirting Rubber

(40 shore 'A' & Tensile Strength: 16 MPA) has better abrasion resistant properties with up to 3-5 times the wear life of black natural skirting rubber. Sold in 15m rolls

Product Code & Description	AU	NZ	Product Code & Description	AU	NZ
10-100-OR 10mm x 100mm x 15m	✓		12-100-OR 12mm x 100mm x 15m	✓	
10-150-OR 10mm x 150mm x 15m	✓		12-150-OR 12mm x 150mm x 15m	√	
10-100-OR 10mm x 150mm x 10m		✓	12-200-OR 12mm x 200mm x 10m		✓
10-200-OR 10mm x 200mm x 15m	✓		12-200-OR 12mm x 200mm x 15m	✓	
10-200-OR 10mm x 200mm x 10m	✓		12-250-OR 12mm x 250mm x 15m	✓	
*Other specifications also available			12-300-OR 12mm x 300mm x 10m		✓
			12-300-OR 12mm x 300mm x 15m	1	T

www.advanced-engineering-group.com

Christchurch 0800 880 233

Brisbane 07 3713 7744

Melbourne 03 9363 1577